

Intimidator® AGM Solutions for Intimidating Battery Needs

Intimidator is a pioneer brand in the development of the form, fit, and function of AGM battery technology. It has been tested and proven to best meet the criteria of the automotive industry.



ADVANCED DURABILITY DESIGNS

- Fortified posts, straps, and welds resist vibration damage
- Maximize current transfer over life of battery



POWER-PERFORM® FULL-FRAME POSITIVE & NEGATIVE PLATES

- Better withstands severe service demands
- Prevents life-robbing electrical shorts from exposed wire



ENHANCED ELECTROLYTE SUSPENSION SYSTEM

- Absorbs more electrolyte, protects internal components
- Micro-porous glass separators prevents acid spills and terminal corrosion

AUTOMOTIVE INTIMIDATOR® AGM BATTERIES

CROUR	PART NO.	PERFORMANCE LEVEL				APPROX.	MAXIMUM OVERALL DIMENSIONS						
GROUP NO.		CCA	RES.	REF. Ca.	20 AH Rate	WEIGHT (lbs.)	Length		Width		Height		FOOTNOTES
		@ 0°F	CAP.				inch	mm	inch	mm	inch	mm	
ABSORBED GLASS MAT (AGM) VALVE REGULATED													
75/86	9A75DT	680	100	835	50	41	9 ¾	248	7 1/16	180	7 15/16	202	2,16,17,18,46
34/78	9A78DT	775	120	955	55	42.5	10 ¾	273	6 %	175	8	203	2,16,17,46
34/78	9A78CDT	700	120	840	55	40.5	10 ¾	273	6 %	175	8	203	2,16,17,46,79
34	9A34	775	120	955	55	41	10 ¾	273	6 %	175	8	203	2,17,46
34R	9A34R	775	120	955	55	41	10 ¾	273	6 %	175	8	203	2,17,46
35/85	9A35/85	680	100	835	50	39	9 ¾	248	6 %	175	7 3/4	197	2,17,18,46
47	9A47	600	100	690	60	39	9 %6	242	6 %	175	7 ½	190	17,22,46
48	9A48	760	120	875	70	45.5	11	278	6 %	175	7 ½	190	17,22,46
49	9A49	850	170	975	92	58.5	13 15/16	354	6 %	175	7 ½	190	17,22,46
65	9A65	775	150	955	75	46	12	305	7 %	187	7 %	194	2,17,46
78	9A78	775	120	955	55	42.5	10 ¾	273	6 %	175	7 1/4	184	2,17,46
94R	9A94R	800	140	920	80	51.5	12 1/16	315	6 %	175	7 ½	190	17,22,46
95R	9A95R	950	190	1090	105	64.5	15 ½	394	6 %	175	7 ½	190	17,22,46
Prius	9A51P	325	60	400	46	30	9 %	238	5	127	8 ¾	222	22,46,J

All batteries have SAE automotive posts unless noted. All batteries in Black cover/Black case except where noted.

FOOTNOTES: 2. Black cover / Gray case 16. Dual terminal universal design 17. Includes handle 18. Includes top adapter 22. Flush manifold vented cover 46. If battery is used on-highway vehicles equiped with two-way radios (such as taxis, police, and emergency vehicles), marine applications, off-highway use, and other non-automotive usage, free warranty replacement period will be 18 months. Free replacement warranty is 12 months in deep-cycle use and 3 months in full electric vehicle use 79. Added durability for heavier cycle service and commercial use J. JIS Terminal "pencil post".

Experience the East Penn Advantage


East Penn's $A^{3 \text{ TM}}$ Advanced-Cubed precision-focused manufacturing approach ensures the process behind the technology delivers critical quality at each stage of battery production. INTIMIDATOR batteries are supported by







11 manufacturing to opininge use uje, pouci, und





www.dekabatteries.com

